

Gutachten 366-0166-14-WIRD
zur Erteilung der ECE (E1) 124R- 000622

ANLAGE: 9.3

Hersteller: Momo S.r.l.

Radtyp: 639

Stand: 12.05.2014



Seite: 1 von 2

Manufacturer : AUDI, QUATTRO GmbH**Wheel dates:**

Wheel size according to standard : 7 J X 16 EH2+ Off set(mm) : 53
 Hole circle (mm)/number of holes : 112/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling circumference (mm)	Valid from Production date
	Wheel identification	Centering type identification					
511253571	PCD 112	Without	57,1		600	1950	04/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : AUDI

Mounting parts : spherical collar bolt M14x1,5, length of shaft 27 mm

Accessories : fasteners series

Tightening torque for fixing parts : 120 Nm

commercial type: **AUDI A3**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
8V	e1*2007/46*0607*..	118	205/55R16	12K; 51G	10B; 11H; 11N; 51A; 711; 714; 721; 73C; 74D; 76V

commercial type: **AUDI A3 CABRIOLET**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
8P	e1*2001/116*0456*..	75 - 147	205/55R16	12K; 51G	10B; 11H; 11N; 51A; 711; 714; 721; 73C; 74D; 76V
8V	e1*2007/46*0612*..	118	205/55R16	12K; 51G	10B; 11H; 11N; 51A; 711; 714; 721; 73C; 74D; 76V

commercial type: **AUDI A3,S3**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
8P	e1*2001/116*0217*..	75 - 147	205/55R16	12K; 51G	10B; 11H; 11N; 51A; 711; 714; 721; 73C; 74D; 76V
8PA	e1*2001/116*0418*..	75 - 147	205/55R16	12K; 51G	10B; 11H; 11N; 51A; 711; 714; 721; 73C; 74D; 76V

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : QUATTRO GmbH

Mounting parts : spherical collar bolt M14x1,5, length of shaft 27 mm

Gutachten 366-0166-14-WIRD
zur Erteilung der ECE (E1) 124R- 000622

ANLAGE: 9.3

Hersteller: Momo S.r.l.

Radtyp: 639

Stand: 12.05.2014



Seite: 2 von 2

Accessories : fasteners series

Tightening torque for fixing parts : 120 Nm

commercial type: **AUDI S3,RS3**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
8P	e1*2001/116*0241*..	110	205/55R16	12K; 51G	10B; 11H; 11N; 51A; 711; 714; 721; 73C; 74D; 76V

Restrictions

- 10B) Apart from tires with an M + S tread, the required minimum speed ranges for the tires to be used, taking load indexes into consideration, can be found in the vehicle documentation, unless deviations have been defined in the scope of application.
- 11H) If the standard spare wheel is used, the car should be driven at moderate speed and for no longer than necessary. The wheel must be fitted with standard fastening elements. When the spare wheel is used on four-wheel-drive vehicles, care should be taken to use only tires with identically sized rolling circumference.
- 11N) The brake and steering systems and the suspension, except for custom suspension springs, must be standard, unless governed by other requirements. For custom suspension springs, a national type approval or a component type approval is necessary; there must be no technical objections to the use of the wheel/tire combination. If the suspension is modified at the time the custom wheels are fitted, this modification and its effect on the fitting of custom wheels must be separately evaluated.
- 12K) The use of snow chains is only permitted if the latter have been approved by the vehicle manufacturer for this wheel/tire combination (cf. operating instructions).
- 51A) The inflation pressure specified by the vehicle manufacturer (see operating instructions or tire inflation pressure indicated on the vehicle) or tire manufacturer must be observed. According to the manufacturer, tires with run-flat properties may only be used in combination with a tire inflation monitoring system.
- 51G) This wheel/tire combination may only be used if this tire has already been entered as the standard in vehicle documents or has been approved by the vehicle manufacturer, see excerpts from EC vehicle approval (EC certificate of compliance). The load index, speed symbol, M+ S identification, the tire makes entered in the vehicle documentation and the remarks and recommendations of the vehicle manufacturer must be observed when this tire size is used.
- 711) The wheels may be balanced on the inner side of the rim only with adhesive weights.
- 714) The wheels may only be balanced on the outer side of the rim by positioning adhesive weights below the drop center.
- 721) The only valves permissible are rubber valves or threaded metal valves with union nuts from the outside which correspond in all critical points to the standards (DIN, E.T.R.T.O or Tire and Rim) and for which a rated valve-hole diameter of 11.3 mm is suitable. The valve may not project over the rim edge.
- 73C) Only tubeless tires may be used.
- 74D) Only the standard wheel-fastening elements may be used.
- 76V) The use of this tire size and offset is only permitted if used as standard.