

Gutachten 366-0166-14-WIRD
zur Erteilung der ECE (E1) 124R- 000622

ANLAGE: 9.1

Hersteller: Momo S.r.l.

Radtyp: 639

Stand: 12.05.2014



Seite: 1 von 3

Manufacturer : SEAT, SKODA, VOLKSWAGEN

Wheel dates:

Wheel size according to standard : 7 J X 16 EH2+ Off set(mm) : 46
 Hole circle (mm)/number of holes : 100/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling circumference (mm)	Valid from Production date
	Wheel identification	Centering type identification					
510046571	PCD 100	Without	57,1		650	1990	04/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : SEAT

Mounting parts : conical collar bolt M14x1,5, length of shaft 27 mm, tapered thread 60 Grad

Accessories : fasteners series

Tightening torque for fixing parts : 120 Nm

commercial type: **TOLEDO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
NH	e11*2007/46*0251*..	55 -90	215/45R16	12K; 51G	from e11*2007/46*0251*01; Limousine; Front wheel drive; 10B; 11H; 11N; 51A; 711; 714; 721; 73C; 74D; 76V

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : SKODA

Mounting parts : conical collar bolt M14x1,5, length of shaft 27 mm, tapered thread 60 Grad

Accessories : fasteners series

Tightening torque for fixing parts : 120 Nm

commercial type: **RAPID**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
NH	e11*2007/46*0250*..	55 -90	215/45R16	12K; 51G	from e11*2007/46*0250*01; Limousine; Front wheel drive; 10B; 11H; 11N; 51A; 711; 714; 721; 73C; 74D; 76V

**Gutachten 366-0166-14-WIRD
zur Erteilung der ECE (E1) 124R- 000622**

ANLAGE: 9.1

Hersteller: Momo S.r.l.

Radtyp: 639

Stand: 12.05.2014



Seite: 2 von 3

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : VOLKSWAGEN

Mounting parts : conical collar bolt M14x1,5, length of shaft 27 mm, tapered thread 60 Grad

Accessories : fasteners series

Tightening torque for fixing parts : 120 Nm

commercial type: **POLO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
6R	e1*2001/116*0510*..	44 -132	215/45R16	12K; 51G	711; 714; 721; 73C; 74D
6R	e1*2007/46*0486*..	44 -77	215/45R16	12K; 51G	10B; 11H; 11N; 51A; 711; 714; 721; 73C; 74D; 76V

Restrictions

- 10B) Apart from tires with an M + S tread, the required minimum speed ranges for the tires to be used, taking load indexes into consideration, can be found in the vehicle documentation, unless deviations have been defined in the scope of application.
- 11H) If the standard spare wheel is used, the car should be driven at moderate speed and for no longer than necessary. The wheel must be fitted with standard fastening elements. When the spare wheel is used on four-wheel-drive vehicles, care should be taken to use only tires with identically sized rolling circumference.
- 11N) The brake and steering systems and the suspension, except for custom suspension springs, must be standard, unless governed by other requirements. For custom suspension springs, a national type approval or a component type approval is necessary; there must be no technical objections to the use of the wheel/tire combination. If the suspension is modified at the time the custom wheels are fitted, this modification and its effect on the fitting of custom wheels must be separately evaluated.
- 12K) The use of snow chains is only permitted if the latter have been approved by the vehicle manufacturer for this wheel/tire combination (cf. operating instructions).
- 51A) The inflation pressure specified by the vehicle manufacturer (see operating instructions or tire inflation pressure indicated on the vehicle) or tire manufacturer must be observed. According to the manufacturer, tires with run-flat properties may only be used in combination with a tire inflation monitoring system.
- 51G) This wheel/tire combination may only be used if this tire has already been entered as the standard in vehicle documents or has been approved by the vehicle manufacturer, see excerpts from EC vehicle approval (EC certificate of compliance). The load index, speed symbol, M+ S identification, the tire makes entered in the vehicle documentation and the remarks and recommendations of the vehicle manufacturer must be observed when this tire size is used.
- 711) The wheels may be balanced on the inner side of the rim only with adhesive weights.
- 714) The wheels may only be balanced on the outer side of the rim by positioning adhesive weights below the drop center.
- 721) The only valves permissible are rubber valves or threaded metal valves with union nuts from the outside which correspond in all critical points to the standards (DIN, E.T.R.T.O or Tire and Rim) and for which a rated valve-hole diameter of 11.3 mm is suitable. The valve may not project over the rim edge.
- 73C) Only tubeless tires may be used.
- 74D) Only the standard wheel-fastening elements may be used.

**Gutachten 366-0166-14-WIRD
zur Erteilung der ECE (E1) 124R- 000622**

ANLAGE: 9.1
Hersteller: Momo S.r.l.

Radtyp: 639
Stand: 12.05.2014



Seite: 3 von 3

76V) The use of this tire size and offset is only permitted if used as standard.