

**Gutachten 366-0166-14-WIRD  
zur Erteilung der ECE (E1) 124R- 000622**

ANLAGE: 9.4

Hersteller: Momo S.r.l.

Radtyp: 639

Stand: 12.05.2014



Seite: 1 von 2

**Manufacturer : AUDI****Wheel dates:**

Wheel size according to standard : 7 J X 16 EH2+

Off set(mm) : 48

Hole circle (mm)/number of holes : 112/5

centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling circumference (mm)	Valid from Production date
	Wheel identification	Centering type identification					
511248571	PCD 112	Without	57,1		670	1990	04/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : AUDI**

Mounting parts : spherical collar bolt M14x1,5, length of shaft 28 mm

Accessories : fasteners series

Tightening torque for fixing parts : 120 Nm

commercial type: **AUDI A3, S3**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
8V	e1*2007/46*0607*..	77-132	205/55R16 91W	12K; 51G	11H; 51A; 711; 714; 723; 73C; 74D; 76V

**Restrictions**

- 11H) If the standard spare wheel is used, the car should be driven at moderate speed and for no longer than necessary. The wheel must be fitted with standard fastening elements. When the spare wheel is used on four-wheel-drive vehicles, care should be taken to use only tires with identically sized rolling circumference.
- 12K) The use of snow chains is only permitted if the latter have been approved by the vehicle manufacturer for this wheel/tire combination (cf. operating instructions).
- 51A) The inflation pressure specified by the vehicle manufacturer (see operating instructions or tire inflation pressure indicated on the vehicle) or tire manufacturer must be observed. According to the manufacturer, tires with run-flat properties may only be used in combination with a tire inflation monitoring system.
- 51G) This wheel/tire combination may only be used if this tire has already been entered as the standard in vehicle documents or has been approved by the vehicle manufacturer, see excerpts from EC vehicle approval (EC certificate of compliance). The load index, speed symbol, M+ S identification, the tire makes entered in the vehicle documentation and the remarks and recommendations of the vehicle manufacturer must be observed when this tire size is used.
- 711) The wheels may be balanced on the inner side of the rim only with adhesive weights.
- 714) The wheels may only be balanced on the outer side of the rim by positioning adhesive weights below the drop center.
- 723) Only threaded metal valves with union nuts from the outside which correspond in all critical points to the standards (DIN, E.T.R.T.O or Tire and Rim) and for which a rated valve-hole diameter of 11.3 mm is suitable are permissible. The valve may not project over the rim edge.

**Gutachten 366-0166-14-WIRD  
zur Erteilung der ECE (E1) 124R- 000622**

**ANLAGE: 9.4**  
Hersteller: Momo S.r.l.

Radtyp: 639  
Stand: 12.05.2014



Seite: 2 von 2

73C) Only tubeless tires may be used.

74D) Only the standard wheel-fastening elements may be used.

76V) The use of this tire size and offset is only permitted if used as standard.