

**Prüfbericht 366-0333-14-WIRD  
zur Erteilung der ECE (E1) 124R- 000771**

**ANLAGE: 9.9**  
Hersteller: Momo S.r.l.

**Anlage 9 - Verwendungsbereich**



Radtyp: 608  
Stand: 20.01.2015

Seite: 1 von 4

**Manufacturer : AUDI, QUATTRO GmbH, VOLKSWAGEN**

**Wheel dates:**

Wheel size according to standard : 7 J X 17 H2 Off set(mm) : 47  
Hole circle (mm)/number of holes : 112/5 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
511247571	PCD112	Without	57,1		665	2150	11/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : AUDI**

Mounting parts : spherical collar bolt M14x1,5, length of shaft 27 mm, diameter 25,6 mm,  
for Type : 8J

Mounting parts : spherical collar bolt M14x1,5, diameter 25,6 mm, for Type : 8J

Tightening torque for fixing parts : 120 Nm

commercial type: **AUDI TT**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
8J	e1*2001/116*0369*..	118 -200	225/50R17 M+S	12K; 51G; 52J	; 10B; 11H; 11N; 51A; 711; 714; 721; 73C; 74D; 76V; 76Z
8J	e1*2001/116*0374*..	147 -184	225/50R17 M+S	12K; 51G; 52J	10B; 11H; 11N; 51A; 711; 714; 721; 73C; 74D; 76V
8J	e1*2001/116*0375*..	184	225/50R17 M+S	12K; 51G; 52J	10B; 11H; 11N; 51A; 711; 714; 721; 73C; 74D; 76V; 76Z

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : QUATTRO GmbH**

Mounting parts : spherical collar bolt M14x1,5, diameter 25,6 mm

Tightening torque for fixing parts : 120 Nm

commercial type: **AUDI TT**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
8J	e1*2001/116*0369*..	118 -200	225/50R17 M+S	12K; 51G; 52J	; 10B; 11H; 11N; 51A; 711; 714; 721; 73C; 74D; 76V; 76Z

**Prüfbericht 366-0333-14-WIRD**  
**zur Erteilung der ECE (E1) 124R- 000771**
**ANLAGE: 9.9**

Hersteller: Momo S.r.l.

Radtyp: 608

Stand: 20.01.2015



Seite: 2 von 4

commercial type: **AUDI TT**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
8J	e1*2001/116*0374*..	147 - 184	225/50R17 M+S	12K; 51G; 52J	10B; 11H; 11N; 51A; 711; 714; 721; 73C; 74D; 76V
8J	e1*2001/116*0375*..	184	225/50R17 M+S	12K; 51G; 52J	10B; 11H; 11N; 51A; 711; 714; 721; 73C; 74D; 76V; 76Z

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : VOLKSWAGEN**

Mounting parts : spherical collar bolt M14x1,5, length of shaft 27 mm, diameter 25,6 mm,  
for Type : 1KP; 1K; 1T

Mounting parts : spherical collar bolt M14x1,5, diameter 25,6 mm,  
for Type : 1T

Accessories : Original bolts/nuts

Mounting parts : spherical collar bolt M14x1,5, diameter 25,6 mm,  
for Type : 1T; 1t

Tightening torque for fixing parts : 120 Nm

commercial type: **GOLF**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1K	e1*2001/116*0242*..	188 - 199	205/50R17	12K; 51G	Only Golf 6; 10B; 11H; 11N; 51A; 711; 714; 721; 73C; 74D; 76V

commercial type: **GOLF PLUS**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1KP	e1*2001/116*0304*..	75 - 118	225/45R17	12K; 51G	Only CrossGolf; Only to e1*2001/116*0304*13; 10B; 11H; 11N; 51A; 711; 714; 721; 73C; 74D; 76V
1KP	e1*2001/116*0304*..	77 - 118	225/45R17	12K; 51G	Only CrossGolf 6; From e1*2001/116*0304*21; 10B; 11H; 11N; 51A; 711; 714; 721; 73C; 74D; 76V

commercial type: **TOURAN**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1t	DE*2007/46*0506*..	66 - 125	225/45R17	12K; 51G	Sportfahrwerk; 10B; 11H; 11N; 51A; 711; 714; 721; 73C; 74D; 76V

**Prüfbericht 366-0333-14-WIRD**  
**zur Erteilung der ECE (E1) 124R- 000771**

ANLAGE: 9.9

Hersteller: Momo S.r.l.

Radtyp: 608

Stand: 20.01.2015



Seite: 3 von 4

commercial type: **TOURAN**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1t	e1*2007/46*0506*..	66 -125	225/45R17	12K; 51G	10B; 11H; 11N; 51A; 711; 714; 721; 73C; 74D; 76V
1T	e1*2001/116*0211*..	66 -125	225/45R17	12K; 51G	10B; 11H; 11N; 51A; 711; 714; 721; 73C; 74D; 76V
1T	e1*2001/116*0211*..	66 -125	225/45R17 91	12K; 51G	from e1*2001/116*0211*23; 10B; 11H; 11N; 51A; 711; 714; 721; 73C; 74D; 76V
1T	e1*2007/46*0357*..	66 -130	225/45R17 91	12K; 51G	10B; 11H; 11N; 51A; 711; 714; 721; 73C; 74D; 76V

**Restrictions**

- 10B) Apart from tires with an M + S tread, the required minimum speed ranges for the tires to be used, taking load indexes into consideration, can be found in the vehicle documentation, unless deviations have been defined in the scope of application.
- 11H) If the standard spare wheel is used, the car should be driven at moderate speed and for no longer than necessary. The wheel must be fitted with standard fastening elements. When the spare wheel is used on four-wheel-drive vehicles, care should be taken to use only tires with identically sized rolling circumference.
- 11N) The brake and steering systems and the suspension, except for custom suspension springs, must be standard, unless governed by other requirements. For custom suspension springs, a national type approval or a component type approval is necessary; there must be no technical objections to the use of the wheel/tire combination. If the suspension is modified at the time the custom wheels are fitted, this modification and its effect on the fitting of custom wheels must be separately evaluated.
- 12K) The use of snow chains is only permitted if the latter have been approved by the vehicle manufacturer for this wheel/tire combination (cf. operating instructions).
- 51A) The inflation pressure specified by the vehicle manufacturer (see operating instructions or tire inflation pressure indicated on the vehicle) or tire manufacturer must be observed. According to the manufacturer, tires with run-flat properties may only be used in combination with a tire inflation monitoring system.
- 51G) This wheel/tire combination may only be used if this tire has already been entered as the standard in vehicle documents or has been approved by the vehicle manufacturer, see excerpts from EC vehicle approval (EC certificate of compliance). The load index, speed symbol, M+ S identification, the tire makes entered in the vehicle documentation and the remarks and recommendations of the vehicle manufacturer must be observed when this tire size is used.
- 52J) This tire size is only permitted with M+S tread
- 711) The wheels may be balanced on the inner side of the rim only with adhesive weights.
- 714) The wheels may only be balanced on the outer side of the rim by positioning adhesive weights below the drop center.
- 721) The only valves permissible are rubber valves or threaded metal valves with union nuts from the outside which correspond in all critical points to the standards (DIN, E.T.R.T.O or Tire and Rim) and for which a rated valve-hole diameter of 11.3 mm is suitable. The valve may not project over the rim edge.
- 73C) Only tubeless tires may be used.

**Prüfbericht 366-0333-14-WIRD  
zur Erteilung der ECE (E1) 124R- 000771**

**ANLAGE: 9.9**  
Hersteller: Momo S.r.l.

Radtyp: 608  
Stand: 20.01.2015



Seite: 4 von 4

74D) Only the standard wheel-fastening elements may be used.

76V) The use of this tire size and offset is only permitted if used as standard.

76Z) This wheel size may only be used in combination with M+S tires